

Specs and details of warehouse 2. WH2

- Warehouse size 27.00X360.00 M.
- Warehouse structure is built by the reinforce concrete.
- Floor load cap. 5,000 kgs/sqm. with hardener surface finish.
- Indoor clearing height is 10.00 M., the total top roof height is 12.00M., the wide span of warehouse is clear without central column.
- Internal road is +1.00M. from the public external road.
- Roofing structure is built by the steel truss and covered by the metal sheet on top roof.
- In-ex warehouse area is painted by the acrylic paint.
- Both sides of windows in warehouse are completed with aluminum frame for incoming sunlight.
- Indoor lighting are hi-bay.
- Indoor MCB for control lighting has total 5 different stations.
- Outdoor lights are covered whole area.
- Warehouse has 5 electric roller shutter doors for normal loading and unloading.
- Service man and woman toilets are built-in warehouse total 5 stations.
- Building has designed for combination between warehouse and factory which can install the overhead crane 20 Tons.
- Column of building has been prepared with the base steel for overhead crane elevation.
- Water supply cap. max. 100M3/H, transformer max cap. 1,000 KVA is equivalent approx 1,500A.
- Main public hydrant inlet water pipe for fire protection has installed at the front of main building.
- Internal hydrant pipelines are covered whole area of warehouses and hose cabinets are fixed at distance of every 48.00M.
- Low and high voltage cables have installed underground.
- Inlet and outlet water pipeline, telephone line, high speed internet line and etc., have installed underground.
- Indoor wiring of cables are covered by wire-duct, cable tray and conduits for standard safety.

www.cng-warehouse.com

Hotline : +66 65 645 7624, +66 89 664 9201 Email : cngwarehouse@gmail.com

