



## Specs and details of warehouse 1 raised floor type. WH1

- Warehouse size approx. 54.50X320.60 M.
- Warehouse structure is built by the reinforce concrete.
- Floor load cap. 5,000 kgs/sqm. with epoxy coating.
- Indoor clearing height is 8.60 M., the total top roof height is 12.00M., the wide span of warehouse is clear without central column.
- Loading and unloading by dock leveler has the raised floor +1.40M. from internal road.
- Internal road is +1.00M. from the public external road.
- Roofing structure is built by the steel truss and covered by the heat insulator and the metal sheet on top roof.
- In-ex warehouse area is painted by the acrylic paint.
- Both sides of windows in warehouse are completed with aluminum frame for incoming sunlight.
- Indoor lighting are hi-bay.
- Indoor MCB for control lighting is completed with 6 different stations.
- Outdoor lights are covered whole area.
- Warehouse has 8 electric roller shutter doors at side with normal loading and unloading platform.
- Warehouse has 9 electric roller shutter doors with the dock leveler at rear side.
- Service man and woman toilets are located nearby the warehouse.
- Water supply cap. max. 100M<sup>3</sup>/H, transformer max cap. 1,000 KVA is equivalent approx 1,500A.
- Main public hydrant inlet water pipe for fire protection has installed at the front of main building.
- Internal hydrant pipelines are covered whole area of warehouses and hose cabinets are fixed at distance of every 48.00M.
- Low and high voltage cables have installed underground.
- Inlet and outlet water pipeline, telephone line, high speed internet line and etc., have installed underground.
- Indoor wiring of cables are covered by wire-duct, cable tray and conduits for standard safety.

**[www.cng-warehouse.com](http://www.cng-warehouse.com)**

Hotline : +66 65 645 7624, +66 89 664 9201

Email : [cngwarehouse@gmail.com](mailto:cngwarehouse@gmail.com)

